



PREMIUM UNIVERSAL TRACTOR HYDRAULIC FLUID (J20C)

Product Description

LUBRIMAR PREMIUM UNIVERSAL TRACTOR HYDRAULIC FLUID (J20C) is formulated with high-viscosity index base stocks and premium performance additives. This multipurpose oil is designed for use in transmissions, differentials, hydraulic, and power-steering units in many different makes of tractors and farm equipment. Designed for all-season use, this multi-grade oil is specialty blended to prevent rust, corrosion, foaming and oxidation. This oil exceeds the performance of John Deere’s J20C specification.

Typical Properties

PARAMETER	TYPICAL
Appearance	Amber, Bright, Free & Clear
Density	0.89 g/cm ³
Viscosity cSt @ 40°C	55
Viscosity cSt @ 100°C	9.50
Pour Point, °C	-42
Flash Point, °C	215
Viscosity Index	147

Exceeds Performance Requirements

John Deere - J20C

New Holland (Ford) - FNHA-2-C-201.00 (M2C134-D), M2C41-B, M2C48-B, M2C53-A, M2C134-A, M2C134-B, M2C134-C, M2C86-B

Massey-Ferguson - M1135, M1141, M1143, M1110, M1127, M1129-A

Case International - MS-1209 – HyTran ULTRA R, MS-1207 – HyTran Plus, JIC-145/MS-1210, JIC-185/MS-1204, MS-1205, MS-1206, B-6

Kubota, White Farm - Q-1826, Q-1705, Q-1766, Q-1802,

Allison C-4, Caterpillar TO-2

Denison HF-O, HF-1, HF-2 A

Sperry Vickers I-286-S, M-2950-S R Sundstrand Hydraulics

Plessey-Sundstrand, Steiger, Versatile, Deutz-Allis, Landini, Fiat-Hesston