



## FULL SYNTHETIC GLOBAL ATF

### DESCRIPTION:

Full Synthetic Global ATF is a full synthetic premium fluid designed for automatic transmissions of all North American, European, and Asian passenger car and commercial vehicles. Full Synthetic Global ATF provides exceptional oxidation, wear, frictional stability, sludge and deposit prevention, and anti-shudder properties required in today's high performance transmissions. It is also designed to deliver premium performance in older transmissions.

### APPLICATIONS:

Full Synthetic Global ATF high viscosity automatic transmission fluid is suitable for use in Ford, GM, Toyota, and many other OEM applications.

Not recommended for use where Ford Type F/G, DCTs, and CVTs fluid is required.

- See table below for Specific Manufacturer's Applications

\* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

### TYPICAL TEST DATA

Product Specifications	Results
Specific Gravity @ 60 °F	0.8495
Viscosity, Kinematic cSt at 40°C	30.2
cSt at 100°C	7.0
Viscosity Index	208
Viscosity, Brookfield cP at -40°C	8,376
Flash Point, °F	360
Pour Point, °C (°F)	-54 (-65)
Color	RED

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.



SPECIFIC MANUFACTURER'S APPLICATIONS

SUITABLE FOR USE CLAIMS	
Aisin Warner AW-1	Allison C-4
Allison TES-295	Allison TES-389, TES-389B
Audi G 052 162, G 052 990, G 055 025	Audi G 055 005, G 055 162, G 052 540
BMW 7045E, BMW ETL-8072B, LA2634, LT71141	BMW 83 22 0 142 516
Chrysler MS-10838 P/N 05142893AA	Chrysler MS-1872, MS-5931, P/N 04883077, MS 9602
DSIH 6p805 (Geely, Ssangyong, Mahindra 6sp)	Ford M
Ford M2C195-A	Ford Part # XL-12
GM AutoTrak II	GM P/N 12345866 (GM 9985835)
GM P/N 89021184, P/N 1052884 (GM 9985010)	GM-IID, IIIG, IIIH
Honda ATF Z-1	Honda DW-1
Hyundai NWS-9638	Hyundai/KIA PSF-3
Hyundai/Kia SP-II, SP-III, JWS 3314, JWS 3317	Hyundai/Kia SP-IV, SPH-IV, SP-IV RR
JASO 1-A	JASO 1-A-LV
JWS 3309 (Aisin Warner)	JWS 3324
Kia Red-1	MAN 339 Type Z-1
MAN 339F, 339 Type V-1	Mazda ATF-M III, ATF-MV
Mercedes GL-450 (ATF 3403)	Mercedes-Benz 236.1, 236.2, 236.3, 236.6, 236.7, 236.9, 236.11,
236.81	Mercedes-Benz 236.12, 236.14, 236.15
Mercedes-Benz 236.3 (P/N 000 989 88 03)	Mercedes-Benz 236.91
Mercedes-Benz; MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9,	236.10 (NAG 1/ Shell 3403), 236.11, 236.81
Mitsubishi ATF-J3, ATF-PA	Mitsubishi PS fluid, Diamond SP-III
Mitsubishi SP-II, SP-III, Dia Queen ATF J2	Nissan 402, Nissan Matic-D, J, K
Nissan MaticS, MaticW	Nissan PSF-II
North American models (DEXRON VI, MERCON LV)	Other North American high viscosity ATF (MERCON V, ATF+4)
PSA B71 2340	Renault DP-0
Saab 93 165 147	Saab P/N 45 30 09 800
Subaru ATF, ATF-HP	Subaru P/N K0209A0080
Suzuki 3314, 3317	Texaco N402 (JATCO), ETL-7045E (BMW 7045E), ETL-8072B
(BMW 5 Sp)	Toyota PSF Type EH P/N 008886-01
Toyota T, T-II, T-III, T-IV	Toyota WS (JWS 3324)
VoithH55.6335	Volvo 4speed (P/N 1161621)
Volvo 5/6 speed (P/N 1161540/1161640)	Volvo 6 speed MY 2011-2013 (P/N 31256774 or 31256675)
Volvo 97340, 97341	VW G 052 162, G 052 990, G 055 025
VW G 052 540, G 055 005, G 055 162	ZF 6 Speed (S671 090 281)
ZF TE-ML 03D, 04D, 05L, 16L, 17C	ZF TE-ML 09
ZF TE-ML 11(3/4/5 speed)	ZF TE-ML 14A
ZF TE-ML 21L	